



14157106

Rocker, lab. field, lens, K.1, ant. matt, lacq.

Technical characteristics

0	mi	tro	10	- n	a	ind	lica	tors	
L.C	วทา	cro	ıs	an	a	ına	ııca	tors	١

Push-buttons	also for KNX applications: push-button, 1gang, and group push-button, 1gang				
Rocker switch/rocker push-button	for rocker push-buttons ; for change- over/intermediate switch				
Materials					
Colour of design line	anthracite				
Material / workmanship	lacquered				
Surface appearance	matt				
Installation, mounting					
Installation mode	clamp fastening				
Equipment					
Lighting	for lighting and monitoring circuit				
Use cases					
Application	Light control				
Use					
Differentiation characteristic 1 - Sales	with labelling field				
Differentiation characteristic 2 - Sales	Lens				
Safety					
REACH conform	Yes				
RoHS conform	Yes				
Halogen free	No				
Identification					
Application, usage	Light control ; Flush-mounted wet-room installation				
Main design line	Berker K.1				
Instructions					
	The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing				
Special note text	set for switches/push-buttons.				
Information text	For labelling with names, notes etc. Labelling field height designed for 6 mm P-touch strip.				