



14177109

Rocker imprint "0", red lens, K.1, p. white glossy

Technical characteristics

Controls and indicators

| | |
|----------------------------------|---|
| Push-buttons | also for KNX applications: group push-button, 1gang |
| Rocker switch/rocker push-button | for multi-pole rocker switches |

Materials

| | |
|-----------------------|-----------------------|
| Colour of design line | polar white |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Surface appearance | glossy |

Installation, mounting

| | |
|-------------------|-----------------|
| Installation mode | clamp fastening |
|-------------------|-----------------|

Equipment

| | |
|----------|-------------------------------------|
| Lighting | for lighting and monitoring circuit |
|----------|-------------------------------------|

Use cases

| | |
|-------------|---------------|
| Application | Light control |
|-------------|---------------|

Use

| | |
|--|----------|
| Differentiation characteristic 2 - Sales | red lens |
|--|----------|

Safety

| | |
|---------------|-----|
| REACH conform | Yes |
| RoHS conform | Yes |
| Halogen free | Yes |

Identification

| | |
|--------------------|---|
| Application, usage | Light control ; Flush-mounted wet-room installation |
| Main design line | Berker K.1 |

Instructions

| | |
|-------------------|---|
| Special note text | The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons. |
|-------------------|---|