



16216074

**Rocker w. 2 lenses attached and imprinted light symbol, Q.x, alu velvety, lacq.**

#### Technical characteristics

#### Controls and indicators

Push-buttons	also for KNX applications: push-button, 1gang, and group push-button, 1gang
Rocker switch/rocker push-button	for rocker push-buttons ; for change-over/intermediate switch

#### Materials

Colour of design line	aluminium
Material / workmanship	lacquered
Surface appearance	velvety

#### Installation, mounting

Installation mode	clamp fastening
-------------------	-----------------

#### Equipment

Lighting	for lighting and monitoring circuit
----------	-------------------------------------

#### Use cases

Application	Light control
-------------	---------------

#### Use

Differentiation characteristic 2 - Sales	Lens
------------------------------------------	------

#### Safety

REACH conform	Yes
RoHS conform	Yes
Halogen free	No

#### Identification

Application, usage	Light control ; Flush-mounted wet-room installation ; KNX - operating systems
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1 ; Berker Q.3 ; Berker Q.7 ; Berker Q.9

#### Instructions

Special note text	The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.
-------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------