



16216076

Rocker imprinted symbol for light, lens, Q.1/Q.3, ant. velvety, lacq.

Technical characteristics

Controls and indicators

Push-buttons	also for KNX applications: push-button, 1gang, and group push-button, 1gang
Rocker switch/rocker push-button	for rocker push-buttons ; for change-over/intermediate switch

Materials

Colour of design line	anthracite
Material / workmanship	lacquered
Surface appearance	velvety

Installation, mounting

Installation mode	clamp fastening
-------------------	-----------------

Equipment

Lighting	for lighting and monitoring circuit
----------	-------------------------------------

Use cases

Application	Light control
-------------	---------------

Use

Differentiation characteristic 2 - Sales	Lens
--	------

Safety

REACH conform	Yes
RoHS conform	Yes
Halogen free	Yes

Identification

Application, usage	Light control ; Flush-mounted wet-room installation ; KNX radio- operating systems
Main design line	Berker Q.1/Q.3/Q.7/Q.9
Secondary design line(s)	Berker Q.1 ; Berker Q.3 ; Berker Q.7 ; Berker Q.9

Instructions

Special note text	The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.
-------------------	---