



16216079

Rocker imprinted symbol for light, lens, Q.1/Q.3, p. white velvety

Technical characteristics

	_	_		
Con	trole	and	indica	store

Push-buttons	also for KNX applications: push-button, 1gang, and group push-button, 1gang		
Rocker switch/rocker push-button	for rocker push-buttons ; for change- over/intermediate switch		
Materials			
Colour of design line	polar white		
Colour	white		
RAL colour	RAL 9010 - Pure white		
Surface appearance	velvety		
Installation, mounting			
Installation mode	clamp fastening		
Equipment			
Lighting	for lighting and monitoring circuit		
Use cases			
Application	Light control		
Use			
Differentiation characteristic 2 - Sales	Lens		
Safety			
REACH conform	Yes		
RoHS conform	Yes		
Halogen free	Yes		
Identification			
Application, usage	Light control ; Flush-mounted wet-room installatio		
Main design line	Berker Q.1/Q.3/Q.7/Q.9		
Secondary design line(s)	Berker Q.1 ; Berker Q.3 ; Berker Q.7 ; Berker Q.9		
Instructions			
Special note text	The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.		