



16216089

Rocker, lens, Q.x, p. white velvety

Technical characteristics

_	_	_		
Con	trole	and	indi	cators

Push-buttons	also for KNX applications: push-button, 1gang, and group push-button, 1gang		
Rocker switch/rocker push-button	for rocker push-buttons, for change over/intermediate switch		
Materials			
Colour of design line	polar white		
Colour	polarwhite		
Colour	white		
RAL colour	RAL 9010 - Pure white		
Material	duroplastic		
Surface appearance	velvety		
Installation, mounting			
Installation mode	clamp fastening		
Equipment			
Lighting	for lighting and monitoring circuit		
Use cases			
Application	Light control		
Use			
Differentiation characteristic 2 - Sales	with lens		
Safety			
REACH conform	Yes		
RoHS conform	Yes		
Identification			
Application, usage	Flush-mounted wet-room installation, Light contro KNX - operating system		
Main design line	Berker Q.1/Q.3/Q.7/Q.9		
Secondary design line(s)	Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9		
Instructions			
Special note text	The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.		