



16402079

Relay switch centre plate for hotel card, 1930/R.classic, p. white glossy

Technical characteristics

Architecture

| | |
|----------------|---|
| Number of keys | 0 |
|----------------|---|

Configuration

| | |
|-------------------------|-------|
| Switch mode | 1pole |
| Antibacterial treatment | No |

Main electrical features

| | |
|-----------------|----------|
| Nominal voltage | 230 V |
| Rated voltage | 230 V AC |
| Frequency | 50/60 Hz |

Electric current

| | |
|--|----------|
| Inductive load at $\cos \varphi = 0.6$ | max. 6 A |
|--|----------|

Dimensions

| | |
|-----------------|--------------|
| Depth | 60 mm |
| Insertion depth | 32 mm |
| Card width | max. 55 mm |
| Card thickness | 0.8...1.2 mm |

Power

| | |
|---------------------------|---------|
| Conventional transformers | 1500 VA |
| Electronic transformers | 1500 W |
| Power consumption | < 0.2 W |

Materials

| | |
|-----------------------|-----------------------|
| Colour of design line | polar white |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Surface appearance | glossy |

Fluorescent bulbs control

| | |
|----------------------------------|--------|
| Compact fluorescent lamps | 500 W |
| Fluorescent lamps in duo circuit | 1500 W |

LED control

| | |
|-----|---|
| LED | illuminated with blue LED if hotel card is not inserted |
|-----|---|

Incandescent bulbs control

| | | |
|--|--|--------|
| 230 V incandescent lamps and halogen lamps | | 1500 W |
| Installation, mounting | | |
| Installation mode | with spreader claws | |
| Connection | | |
| Screw terminals (max.) | 2 x 2,5 mm² | |
| Type of connection | with screw-in lift terminals | |
| Settings | | |
| Delay time incrementally adjustable | 0, 15, 30, 60 s | |
| Setting | with potentiometer for incremental adjustment of delay time | |
| Equipment | | |
| Lighting | for illumination | |
| Potential-free | with potential-free contact | |
| Centre plates / central plates | with centre plate Ø 58 mm | |
| Use cases | | |
| Application | Light control ; Hotel application | |
| Safety | | |
| REACH conform | No | |
| RoHS conform | Yes | |
| Halogen free | No | |
| Use conditions | | |
| Operating temperature | -5...50 °C | |
| Storage/transport temperature | -25...70 °C (storage at > 45°C reduces the service life) | |
| Identification | | |
| Application, usage | Light control | |
| Main design line | Serie 1930/R.classic | |
| Secondary design line(s) | Serie 1930 ; Series R.classic | |
| Instructions | | |
| Special note text | Note: When integrating this product into the Serie 1930, the 1gang frame for centre plate Ø 58 mm, order no.: 1382 0... may only be used. Installation in multiple combinations of the Serie 1930 is not possible! | |