



16512049

**Rocker f.accessible const., tactile symb. f.light, clearlens,R.1/R.3,p.white gl.**

#### Technical characteristics

#### Controls and indicators

Push-buttons	also for KNX applications: push-button, 1gang
Rocker switch/rocker push-button	for illuminated rocker push-buttons

#### Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Material for printing	ASA polar white

#### Installation, mounting

Installation mode	clamp fastening
-------------------	-----------------

#### Settings

Shading parameter	R1_biały
Laser parameter	R1_weiß

#### Equipment

Type of configuration	Laserdruck
Lighting	for lighting and monitoring circuit

#### Use cases

Barrier-free building	based on DIN 18040
Application	Barrier-free application, Light control

#### Use

Differentiation characteristic 1 - Sales	with tactile symbol for light
Differentiation characteristic 2 - Sales	with clear lens

#### Identification

Application, usage	Flush-mounted wet-room installation, Light control
Main design line	Berker R.1/R.3/R.8
Secondary design line(s)	Berker R.1, Berker R.3, Berker R.8

#### Instructions

Special note text	The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.
-------------------	---