



16512069

Rocker f. accessible const., tactile symb. f. door,clearlens,R.1/R.3,p.white gl.

Technical characteristics

Controls and indicators

Push-buttons	also for KNX applications: push-button, 1gang
Rocker switch/rocker push-button	for illuminated rocker push-buttons

Materials

Colour of labelling	105,105,105
Colour of design line	polar white
Colour	white
RAL colour	RAL 9010 - Pure white
Material for printing	ASA polar white
Surface appearance	glossy

Installation, mounting

Installation mode	clamp fastening
-------------------	-----------------

Settings

Shading parameter	R1_biały
Laser parameter	R1_weiß

Equipment

Type of configuration	Laserdruck
-----------------------	------------

Use cases

Barrier-free building	based on DIN 18040
Application	Barrier-free application ; Light control

Use

Differentiation characteristic 1 - Sales	with tactile symbol for door
Differentiation characteristic 2 - Sales	with clear lens

Safety

REACH conform	Yes
RoHS conform	Yes
Halogen free	Yes

Identification

Application, usage	Flush-mounted wet-room installation ; Light control
Main design line	Berker R.1/R.3/R.8
Secondary design line(s)	Berker R.1 ; Berker R.3 ; Berker R.8

Instructions

Special note text

The IP44 degree of protection can only be achieved
in conjunction with the appropriate neon,
incandescent or LED lamp unit, as well as a sealing
set for switches/push-buttons.