



16612049

Rocker f.accessible const., guide f.mouth-held rod,clearlens,R.1/R.3,p.white gl.

Technical characteristics

Controls and indicators

Push-buttons	also for KNX applications: push-button, 1gang, and group push-button, 1gang
Rocker switch/rocker push-button	for change-over/intermediate switch, for rocker push-buttons

Materials

Colour of design line	polar white
Colour	polarwhite
Colour	white
RAL colour	RAL 9010 - Pure white
Material	thermoplastic
Material for printing	ASA polar white

Installation, mounting

Installation mode	clamp fastening
-------------------	-----------------

Settings

Shading parameter	R1_biały
Laser parameter	R1_weiß

Equipment

Type of configuration	Laserdruck
Lighting	for lighting and monitoring circuit

Use cases

Barrier-free building	based on DIN 18040
Application	Barrier-free application, Light control

Use

Differentiation characteristic 1 - Sales	with guide for mouth-held rod
Differentiation characteristic 2 - Sales	with clear lens

Identification

Application, usage	Flush-mounted wet-room installation
Main design line	Berker R.1/R.3/R.8
Secondary design line(s)	Berker R.1, Berker R.3, Berker R.8

Instructions

Special note text	The IP44 degree of protection can only be achieved in conjunction with the appropriate neon, incandescent or LED lamp unit, as well as a sealing set for switches/push-buttons.
-------------------	---