



1686

LED unit 230 V, for switches/push-buttons, light control, white

Technical characteristics

Controls and indicators

Rocker switch/rocker push-button	for rocker push-buttons and multiple rockers push-buttons, except order no. 503404, 503808 ; for change-over/intermediate switch and on/off switch, 2-pole, 10 AX
----------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------

Main electrical features

Rated current	1 mA
---------------	------

Endurance

Service life of the LED	≈ 100000 h
-------------------------	------------

Materials

Colour independent of design lines	white
------------------------------------	-------

Equipment

Lighting	for lighting and monitoring circuit
Combination rocker switches/rocker push-buttons	for series switch illuminated

Use cases

Application	Barrier-free application ; HVAC-control ; Light control
-------------	---------------------------------------------------------

Safety

REACH conform	Yes
RoHS conform	Yes

Identification

Application, usage	Surface-mounted wet-room installation ; Light control
Main design line	Light control
Secondary design line(s)	Light control ; ACCESSORIES

Instructions

Special note text	Refer to the overview for the matching flush-mounted inserts. ; these marked articles (see symbol) are only suitable for the water-protected flush-mounted installation IP44 in conjunction with the corresponding seal, frame and contact protection box (imprint "IP44").
-------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Information text	When several LED units are used, the LED current may result in malfunctioning of the relay/pulse relay. Remedy: Carry along a neutral conductor or connect a capacitor 230 V (1 µF per 10 mA LED current) in parallel with the coil.
------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------