



1686

## LED unit 230 V, for switches/push-buttons, light control, white

### Technical characteristics

#### Architecture

Fixing mode flush-mounting

#### Controls and indicators

Rocker switch/rocker push-button for rocker push-buttons and multiple rockers push-buttons, except order no. 503404, 503808, for change-over/intermediate switch and on/off switch, 2-pole, 10 AX

#### Main electrical features

Rated current 1 mA

#### Endurance

Service life of the LED  $\approx$  100000 h

#### Materials

Colour independent of design lines white

RAL colour RAL 1013 - Oyster white

#### Equipment

Lighting for lighting and monitoring circuit

Combination rocker switches/rocker push-buttons for series switch illuminated

#### Use cases

Application Barrier-free application, HVAC-control, Light control

#### Identification

Application, usage Surface-mounted wet-room installation, Light control

Main design line Light control

Secondary design line(s) Light control, ACCESSORIES

#### Instructions

Special note text Refer to the overview for the matching flush-mounted inserts. ; these marked articles (see symbol) are only suitable for the water-protected flush-mounted installation IP44 in conjunction with the corresponding seal, frame and contact protection box (imprint "IP44").

Information text When several LED units are used, the LED current may result in malfunctioning of the relay/pulse relay. Remedy: Carry along a neutral conductor or connect a capacitor 230 V (1  $\mu$ F per 10 mA LED current) in parallel with the coil.