



29537004

LED signal light, white lighting, K.5, stainless steel matt, lacq.

Technical characteristics

Architecture

Fixing mode	flush-mounting
-------------	----------------

Main electrical features

Rated voltage	230 V AC
---------------	----------

Frequency	50/60 Hz
-----------	----------

Power

Power consumption	at 230 V~, 50 Hz - max. 1 W
-------------------	-----------------------------

Materials

Colour of design line	stainless steel
-----------------------	-----------------

Colour	Stainless steel
--------	-----------------

Colour	stainless steel optics
--------	------------------------

RAL colour	RAL 9022 - Pearl light grey
------------	-----------------------------

Material / workmanship	lacquered
------------------------	-----------

Material	Plastic/metal
----------	---------------

Surface appearance	matt
--------------------	------

LED control

Quantity LED lamps	4
--------------------	---

Installation, mounting

For installation in standard wall boxes	according to DIN 49073-1
---	--------------------------

Connection

Conductor cross-section	2.5 mm ²
-------------------------	---------------------

Settings

Setting	Brightness modifiable via potentiometer
---------	---

Equipment

Lighting	Light colour cold white
----------	-------------------------

Switches / socket outlets	switchable via separate switch
---------------------------	--------------------------------

Use cases

Application	Light control
-------------	---------------

Safety

REACH conform	Yes
---------------	-----

RoHS conform	Yes
--------------	-----

temperatur

Ambient temperature -5...40 °C

Identification

Main design line Berker K.5