



303808

## Double change-over switch, isolated input terminals, light control

### Technical characteristics

#### Architecture

Type of control unit	double rocker
Fixing mode	flush-mounting

#### Configuration

Switch mode	double off/change-over, isolated input terminals
Antibacterial treatment	No

#### Compatibility

IFTTT support available	No
-------------------------	----

#### Controls and indicators

Push-buttons	No
--------------	----

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz

#### Electric current

Switching current	10 AX (100 W Self Ballasted Lamp (SBL))
-------------------	---

#### Dimensions

Depth	41.6 mm
Contact spacing	> 3 mm
Height	71 mm
Width	71 mm

#### Materials

Material	Plastic/metal
Surface appearance	matt

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60669-1
Connection terminals	according to VDE 0632-1
Type of connection	with screw terminals
Type of connection	Screw connection

**Equipment**

---

Lighting	for illumination
Heating switch	No

---

**Use cases**

---

Application	Light control
-------------	---------------

---

**Safety**

---

Protection index IP	IP20
Impact strength	IK07

---

**Identification**

---

Application, usage	Light control
Main design line	Light control

---

**Instructions**

---

Information text	spreader claws, insulated to the supporting ring, self-resetting
------------------	--

---