



## 3315417009

## VGA soc. out., screw-in lift terminals, K.1, p. white glossy

## **Technical characteristics**

Outlet	with straight outlet
Plug type	S-VGA compatible
Connectors / jacks	with 15pole D-subminiature jack (front)
Frequency	
Frequency range video	max. 160 MHz
Screen	
Resolution	max. 1280 x 1024 px
Materials	
Colour of design line	polar white
RAL colour	RAL 9010 - Pure white
Surface appearance	glossy
Installation, mounting	
Installation mode	without spreader claws ; for screw fastening
Connection	
Conductor cross-section	max. 1.5 mm²
Type of connection	with screw-in lift terminals for connection to 15-core VGA cable
Equipment	
Supporting plate / Supporting ring	with supporting ring
Use	
Differentiation characteristic 3 - Sales	with screw-in lift terminals
Safety	
REACH conform	Yes
RoHS conform	Yes
Identification	
Application, usage	Communication technology
Main design line	Berker K.1

## Instructions

For connecting PCs, notebooks, etc. to display devices such as monitors (including LCD monitors) and projectors.; Observe the instructions of the cable and device manufacturers for maximum VGA cable lengths!; Fränkische: "Multimedia tube" for laying pre-assembled connection cable, Art. no. 294.10.092; Installation recommendation: Kaiser: "Electronic box" for compliance with the permissible bending radii, Art. No. 1068-02 or 9062-74

Information text