



41108914

## SCHUKO soc.out. LED+ZSV impr.,labfield,enhncd contact prot. S1/B3/7

### Technical characteristics

#### Architecture

|             |                        |
|-------------|------------------------|
| Design      | according to DIN 49440 |
| Fixing mode | flush-mounting         |

#### Configuration

|                   |   |
|-------------------|---|
| Number of modules | 1 |
|-------------------|---|

#### Main electrical features

|                 |          |
|-----------------|----------|
| Nominal voltage | 250 V    |
| Rated voltage   | 250 V AC |
| Frequency       | 50/60 Hz |
| Rated current   | 16 A     |

#### Electric current

|               |      |
|---------------|------|
| Rated current | 16 A |
|---------------|------|

#### Dimensions

|   |       |
|---|-------|
| Insertion depth                         | 32 mm |
| Installation depth, flush-mounted boxes | 31 mm |

#### Cover, door

|       |                     |
|-------|---------------------|
| Cover | Central cover plate |
|-------|---------------------|

#### Materials

|                              |                          |
|------------------------------|--------------------------|
| Design lines special colours | orange                   |
| Colour                       | orange                   |
| Colour                       | orange                   |
| RAL colour                   | RAL 2003 - Pastel orange |
| Material                     | duroplastic              |
| Surface appearance           | glossy                   |
| Metallic colour              | No                       |

#### Installation, mounting

|                   |                     |
|-------------------|---------------------|
| Installation mode | with spreader claws |
|-------------------|---------------------|

#### Connection

|                      |                              |
|----------------------|------------------------------|
| Connection terminals | according to VDE 0620-1      |
| Type of connection   | with screw-in lift terminals |

#### Use

|  |                      |
|--|----------------------|
| Differentiation characteristic 1 - Sales | with labelling field |
|--|----------------------|

---

**Standards**

Execution SV, ZSV

according to VDE 0100-710

---

**Safety**

IK protection code against mechanical impacts

02

Protection index IP

IP20

Protection

Enhanced contact protection

With enhanced contact protection

Yes

---

**Identification**

Main design line

Berker S.1/B.3/B.7

Secondary design line(s)

Berker S.1 ; Berker B.3 ; Berker B.7

---

**Instructions**

Information text

Labelling field height arranged for P-touch strips 6 mm. ; Insert colour-coded.