



## FCC soc. out., 2 x 8 (4)-pole, cat.3, com-tech, white

## **Technical characteristics**

| Architecture             |                               |
|--------------------------|-------------------------------|
| Design to                | according to DIN EN 60603-7   |
| Connectivity             |                               |
| Outlet                   | with 45° oblique outlet       |
| Plug type                | for RJ11, RJ12 and RJ45 plugs |
| Connectors / jacks       | parallel contacted sockets    |
| Main electrical features |                               |
| Rated voltage            | 125 V DC                      |
| Rated current            | 1 A                           |
| Dimensions               |                               |
| Insertion depth          | 21.5 mm                       |
| Frequency                |                               |
| Transmission bandwidth   | max. 16 MHz                   |
| Resistance               |                               |
| Transition resistance    | < 20 mΩ                       |
| Materials                |                               |
| Colour                   | white                         |
| Installation, mounting   |                               |
| Installation mode        | with spreader claws           |
| Connection               |                               |
| Type of connection       | with screw terminals          |
| Cat.3                    | according to DIN EN 50173     |
| Cat.3 to                 | according to TIA/IAE-568-B.2  |
| Cable                    |                               |
| Conductor Ø              | max. 1 mm                     |
| Safety                   |                               |
| Protection               | No                            |
| Identification           |                               |
| Application, usage       | Communication technology      |
| Main design line         | Communication technology      |