



472140

## Double SCHUKO socket outlet, surface-mounted, white glossy

### Technical characteristics

#### Architecture

Design	according to DIN 49440
Fixing mode	surface-mounting

#### Configuration

Hollow base	without hollow base
Number of modules	2

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC
Frequency	50/60 Hz
Rated current	16 A

#### Electric current

Rated current	16 A
---------------	------

#### Cover, door

Cover	Complete housing
-------	------------------

#### Materials

Colour independent of design lines	white
Colour	white
Colour	white
RAL colour	RAL 1013 - Oyster white
Material	duroplastic

#### Installation, mounting

Opening	knock out opening for entry at top and bottom
Installation mode	for vertical and horizontal mounting, for screw fastening

#### Connection

Connection terminals	according to IEC 60884-1
Connection terminals	according to VDE 0620-1
Type of connection	with plug-in terminals

#### Cable

Wire	with line and duct entry
------	--------------------------

#### Safety

IK protection code against mechanical impacts	02
Protection index IP	IP20
Protection	without enhanced contact protection
With enhanced contact protection	No
<b>Identification</b>	
Application, usage	Dry surface-mounted installation
Main design line	Surface-mounted