



503503

## Double mom. Cont. Switch

### Technical characteristics

#### Architecture

Type of control unit double rocker

#### Functions

Switching angle 3.5 °

#### Configuration

Switch mode 2 NO contacts, separate input terminals

Antibacterial treatment No

#### Compatibility

IFTTT support available No

#### Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

#### Electric current

Momentary-contact current 10 A

#### Dimensions

Depth 41.6 mm

Insertion depth 31.7 mm

Height 71 mm

Width 71 mm

#### Installation, mounting

Installation mode with spreader claws

#### Connection

Connection terminals according to IEC 60669-1

Connection terminals according to VDE 0632-1

Type of connection with plug-in terminals

Type of connection Quickconnect

#### Scope of delivery

With lamp No

#### Equipment

Quantity of NC contacts 1

Quantity of NO contacts 1

can be illuminated using neon lamp, incandescent or LED unit with N terminal ; for lighting and monitoring circuit

Lighting

---

**Use cases**

---

Application Light control

---

**Safety**

---

REACH conform Yes

---

RoHS conform Yes

---

Halogen free Yes

---

**Identification**

---

Application, usage Light control

---

Main design line Light control

---

**Instructions**

---

Information text spreader claws, insulated to the supporting ring, self-resetting