



505101

**Push-button insert f. hotel card switch cover 10 A, NO cont. w. 2 signal cont.**

**Technical characteristics**

**Architecture**

Type of control unit	Hotel card
Number of keys	0

**Configuration**

Switch mode	NO, with 2 separate signalling contacts
Antibacterial treatment	No

**Compatibility**

IFTTT support available	No
-------------------------	----

**Main electrical features**

Nominal voltage	250 V
Rated voltage	250 V AC

**Electric current**

Momentary-contact current	10 A
---------------------------	------

**Dimensions**

Depth	41 mm
Insertion depth	31.2 mm
Height	71 mm
Width	71 mm

**Connection**

Type of connection	with plug-in terminals
--------------------	------------------------

**Equipment**

Lighting	for lighting and monitoring circuit ; can be illuminated using neon and glow lamp unit with N-terminal
----------	--

**Use cases**

Application	Light control
-------------	---------------

**Safety**

REACH conform	Yes
RoHS conform	Yes
Halogen free	Yes

**Identification**

Application, usage	Light control
--------------------	---------------

**Instructions**

---

Information text

Neon and glow lamp units with N-terminal see module inserts accessories. ; For neon and incandescent lamp units with N-terminal, see module insert accessories. More versions available on request.