



505103

Push-button insert for hotel card switch cover, Module inserts

Technical characteristics

Type of control unit	Hotel card
Number of keys	0
Configuration	
Switch mode	NO, with 2 separate signalling contacts
Antibacterial treatment	No
Compatibility	
IFTTT support available	No
Main electrical features	
Nominal voltage	250 V
Rated voltage	250 V AC
Electric current	
Momentary-contact current	2 A
Momentary-contact current Dimensions	2 A
Dimensions	
Dimensions Depth	41 mm
Dimensions Depth Insertion depth	41 mm 31.2 mm
Depth Insertion depth Height	41 mm 31.2 mm 71 mm
Depth Insertion depth Height Width	41 mm 31.2 mm 71 mm
Dimensions Depth Insertion depth Height Width Materials	41 mm 31.2 mm 71 mm 71 mm
Dimensions Depth Insertion depth Height Width Materials Material	41 mm 31.2 mm 71 mm 71 mm
Dimensions Depth Insertion depth Height Width Materials Material Installation, mounting	41 mm 31.2 mm 71 mm 71 mm Plastic/meta
Dimensions Depth Insertion depth Height Width Materials Material Installation, mounting	41 mm 31.2 mm 71 mm 71 mm Plastic/meta
Dimensions Depth Insertion depth Height Width Materials Material Installation, mounting Installation mode Connection	41 mm 31.2 mm 71 mm 71 mm Plastic/meta with spreader claws
Dimensions Depth Insertion depth Height Width Materials Material Installation, mounting Installation mode	41 mm 31.2 mm 71 mm 71 mm Plastic/meta

for lighting and monitoring circuit, can be illuminated using neon and glow lamp unit with N-terminal

0

Use cases

Lighting

Equipment

Quantity of NC contacts

Quantity of NO contacts

Application	Light control, Hotel application
Safety	
Protection index IP	IP20
Identification	
Application, usage	Light control
Main design line	Light control