



505103

## Push-button insert for hotel card switch cover, Module inserts

### Technical characteristics

#### Architecture

Type of control unit	Hotel card
Number of keys	0

#### Configuration

Switch mode	NO, with 2 separate signalling contacts
Antibacterial treatment	No

#### Compatibility

IFTTT support available	No
-------------------------	----

#### Main electrical features

Nominal voltage	250 V
Rated voltage	250 V AC

#### Electric current

Momentary-contact current	2 A
---------------------------	-----

#### Dimensions

Depth	41 mm
Insertion depth	31.2 mm
Height	71 mm
Width	71 mm

#### Installation, mounting

Installation mode	with spreader claws
-------------------	---------------------

#### Connection

Connection terminals	according to IEC 60669-1
Connection terminals	according to VDE 0632-1
Type of connection	with plug-in terminals

#### Equipment

Quantity of NC contacts	0
Quantity of NO contacts	1

Lighting	for lighting and monitoring circuit ; can be illuminated using neon and glow lamp unit with N-terminal
----------	--

#### Use cases

Application	Light control ; Hotel application
-------------	-----------------------------------

**Safety**

---

REACH conform	Yes
RoHS conform	Yes
Halogen free	Yes

**Identification**

---

Application, usage	Light control
Main design line	Light control