



6765107004

Soc.out. earth.pin+LED orient.,enhncd contact prot.,screw-in lift ,K5,steel,lacq

Technical characteristics

Architecture

Number of poles 2pole + earth

Configuration

Number of modules 1

Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

Frequency 50/60 Hz

Rated current 16 A

Dimensions

Insertion depth 32 mm

Power

Power consumption 0.25 W/0.35 VA

Cover, door

Cover Central cover plate

Detection

Sensor integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness

Materials

Colour of design line stainless steel

Material / workmanship lacquered

Surface appearance matt

Lighting control

Switch-off brightness ≈ 4 lx

Switch-on brightness ≈ 2 lx

Light intensity (white) 0.2 cd

LED control

LED long service life of the LED ; white LED light

Installation, mounting

Installation mode with spreader claws

Connection

| | |
|---|--|
| Conductor cross-section (rigid) | max. 2.5 mm ² |
| Connection terminals | according to IEC 60884-1 |
| Type of connection | with screw-in lift terminals |
| Cable | |
| Wiring | through-wiring possible, therefore also ideal for retrofitting |
| Equipment | |
| Lighting | additional benefit by combination of a socket outlet with an orientation light |
| Use | |
| Differentiation characteristic 2 - Sales | enhanced contact protection |
| Differentiation characteristic 3 - Sales | Screw-in lift terminals |
| Safety | |
| IK protection code against mechanical impacts | 05 |
| REACH conform | Yes |
| RoHS conform | Yes |
| Halogen free | No |
| Protection | Enhanced contact protection |
| With enhanced contact protection | Yes |
| Identification | |
| Main design line | Berker K.5 |
| Instructions | |
| Information text | Caution! Items with special flush-mounted insert. Centre plates with LED orientation lights are not compatible with the standard socket outlets. |