



75142329



IP20



Technical characteristics

Functions

With room temperature controller No

Function for switch, push-button, dimmer and shutter functions

Light scenes retrieval, adjustment and storage of 8 light scenes

Compatibility

Extension unit extension unit for light scene push-button

Controls and indicators

With LED indication Yes

Number of buttons 2

Operation one push-button operation for switching, pushing, shutters and dimming

Dimensions

Labelling field length (W x H) 56.4 x 26.8 mm

Height 71 mm

Width 71 mm

Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display No

Materials

Colour of labelling 105,105,105

Colour of design line polar white

RAL colour RAL 9010 - Pure white

Material for printing Paper

Surface appearance velvety

Type of surface treatment untreated

Material family Plastic

LED control

LED with white operation LED and 4 amber status LEDs

Settings

Supported configuration modes system

Parameterisation single and two push-button operation parameterisable

Scope of delivery

Bus connection included	Yes
-------------------------	-----

Equipment

Number of actuation points	4
----------------------------	---

With anti-theft/dismantling protection	Yes
----------------------------------------	-----

Type of configuration	Beschriftungsfeld(er) - Folie
-----------------------	-------------------------------

Product type:	product type: push-button 2gang
---------------	---------------------------------

Controller extension unit	usable as thermostat extension unit
---------------------------	-------------------------------------

Use

Differentiation characteristic 1 - Sales	with labelling fields
------------------------------------------	-----------------------

Differentiation characteristic 3 - Sales	with integral bus coupling unit
------------------------------------------	---------------------------------

Safety

Protection	with dismantling protection
------------	-----------------------------

Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Identification

Application, usage	KNX - operating systems
--------------------	-------------------------

Product family	product family: push-button
----------------	-----------------------------

Main design line	KNX - Berker Q.1/Q.3
------------------	----------------------

Secondary design line(s)	Berker Q.1 ; Berker Q.3 ; Berker Q.7
--------------------------	--------------------------------------

Instructions

Information text	Labelling field sheet, order no. 9498 30 02, available separately.
------------------	--------------------------------------------------------------------