











## **Technical characteristics**

	_						
_		 m	0	ы	0	m	c

Functions	
With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions
Light scenes	retrieval, adjustment and storage of 8 light scenes
Compatibility	
Extension unit	extension unit for light scene push-button
Controls and indicators	
With LED indication	Yes
Number of buttons	2
Operation	one push-button operation for switching, pushing, shutters and dimming
Dimensions	
Labelling field length (W x H)	56.4 x 26.8 mm
Height	71 mm
Width	71 mm
Measurement	
Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
Screen	
With display	No
Materials	
Colour of labelling	105,105,105
Colour of design line	polar white
RAL colour	RAL 9010 - Pure white
Material for printing	Paper
Surface appearance	velvety
Type of surface treatment	untreated
Material family	Plastic
LED control	
LED	with white operation LED and 4 amber status LEDs
Settings	
Supported configuration modes	system
Parameterisation	single and two push-button operation parameterisable

Scope of delivery	
Bus connection included	Yes
Equipment	
Number of actuation points	4
With anti-theft/dismantling protection	Yes
Type of configuration	Beschriftungsfeld(er) - Folie
Product type:	product type: push-button 2gang
Controller extension unit	usable as thermostat extension unit
Use	
Differentiation characteristic 1 - Sales	with labelling fields
Differentiation characteristic 3 - Sales	with integral bus coupling unit
Safety	
Protection	with dismantling protection
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker Q.1/Q.3
Secondary design line(s)	Berker Q.1 ; Berker Q.3 ; Berker Q.7
Instructions	
	Labelling field shoot order no. 0409 20.02 available

Information text