




75142860

**IP20**



**Touch sensor, 2-gang comf, intg bus coupling unit, KNX - R.1, glass p. white**

**Technical characteristics**

**Functions**

With room temperature controller	Yes
----------------------------------	-----

Function	for switch, push-button, dimmer and shutter functions ; Blocking function for sensor surface e.g. for cleaning the glass surface
----------	--

**Compatibility**

Extension unit	extension unit for light scene push-button
----------------	--

**Controls and indicators**

With LED indication	Yes
---------------------	-----

Number of buttons	0
-------------------	---

Operation	operation by gently touching the sensor surfaces on the white LED
-----------	---

**Dimensions**

Depth	23 mm
-------	-------

Height	152 mm
--------	--------

Width	81 mm
-------	-------

**Power**

Current consumption	12.5 mA
---------------------	---------

**Measurement**

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
-------------------	---

**Screen**

With display	Yes
--------------	-----

**Materials**

Colour of design line	glass polar white
-----------------------	-------------------

Colour	white
--------	-------

RAL colour	RAL 9010 - Pure white
------------	-----------------------

Surface appearance	glossy
--------------------	--------

**LED control**

LED	with blue operation LED and 4 white status LEDs
-----	---

**Installation, mounting**

Installation mode	for vertical mounting
-------------------	-----------------------

**Connection**

Bus coupling unit	with integral bus coupling unit
Bus connection	bus connection via connecting terminal
<b>Scope of delivery</b>	
Bus connection included	Yes
<b>Accessories included</b>	
Matching products	for additional products to complement the installation in matching colours/materials, refer to the Design platform R.1/R.3 ; for suitable frames in the same "style" for additional applications, see the Design line R.x
<b>Equipment</b>	
Number of actuation points	4
With anti-theft/dismantling protection	Yes
<b>Use</b>	
Differentiation characteristic 3 - Sales	with integral bus coupling unit
<b>Safety</b>	
REACH conform	Yes
RoHS conform	Yes
<b>Use conditions</b>	
Operating temperature	-5...45 °C
Temperature	temperature measurement via internal temperature sensor or external communication object ; integrated temperature sensor for operation as controller extension unit ; additional connection for external temperature sensor
<b>Identification</b>	
Application, usage	KNX - operating systems
Main design line	KNX - Berker R.1
Secondary design line(s)	KNX ; Berker R.1