




75142935

IP20



KNX glass sensor 2gang comf, intg bus coupling unit, KNX-TS sensor, glass black

Technical characteristics

Architecture

Fixing mode flush-mounting

Functions

With room temperature controller Yes

Function for switch, push-button, dimmer and shutter functions, Blocking function for sensor surface e.g. for cleaning the glass surface

Compatibility

Extension unit extension unit for light scene push-button

Controls and indicators

With LED indication Yes

Number of buttons 0

Operation operation by gently touching the sensor surfaces on the white LED

Dimensions

Depth 37.7 mm

Depth 5.7 mm

Dimensions (W x H x D) 86 x 160 x 5.7 mm

Height 160 mm

Width 86 mm

Power

Current consumption 12.5 mA

Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display No

Materials

Colour of labelling 217,217,217

Colour of design line glass black

Colour black

RAL colour RAL 9005 - Jet black

Material glass

Surface appearance glossy/matt

LED control

LED	with blue operation LED and 4 white status LEDs
-----	---

Installation, mounting

Installation mode	for vertical mounting
-------------------	-----------------------

Connection

Bus coupling unit	with integral bus coupling unit
Bus connection	bus connection via connecting terminal

Scope of delivery

Bus connection included	Yes
-------------------------	-----

Accessories included

Matching products	for glass frames in the same "style" for additional applications, see the Design line B.7, for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x
-------------------	---

Equipment

Number of actuation points	4
With anti-theft/dismantling protection	Yes
Type of configuration	Laserdruck

Use

Differentiation characteristic 3 - Sales	with integral bus coupling unit
--	---------------------------------

Use conditions

Operating temperature	-5...45 °C
Temperature	temperature measurement via internal temperature sensor or external communication object, integrated temperature sensor for operation as controller extension unit, additional connection for external temperature sensor

Identification

Application, usage	KNX - operating systems
Main design line	KNX - Berker TS Sensor - configured
Secondary design line(s)	KNX, Berker TS Sensor

Instructions

Information text	Only suitable for KNX.
------------------	------------------------