





75143326









Technical characteristics

_						
F	 n	-	Ť١	0	n	C

With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions
Light scenes	retrieval, adjustment and storage of 8 light scenes
Compatibility	

Extension unit	extension unit for light scene push-button
----------------	--

Controls and indicators

With LED indication	Yes
Number of buttons	3
Operation	one push-button operation for switching, pushing,
Operation	one push-button operation for switching, pushing, shutters and dimming

Dimensions

Labelling field length (W x H)	56.4 x 17 mm
Height	71 mm
Width	71 mm

Measurement

	value transmitter for dimming, position, brightness
Value transmitter	and temperature values 1 and 2 byte

Screen

With display	No
With display	INO

Materials

Materials	
Colour of labelling	217,217,217
Colour of design line	anthracite
Material for printing	Paper
Surface appearance	velvety
Material family	Plastic

LED control

Settings

Supported configuration modes	system
-------------------------------	--------

single and two push-button operation parameterisable

Scope of delivery

Parameterisation

Bus connection included Yes **Equipment** Number of actuation points 6 With anti-theft/dismantling protection Yes Type of configuration Beschriftungsfeld(er) - Folie Product type: product type: push-button 3gang Controller extension unit usable as thermostat extension unit Use Differentiation characteristic 1 - Sales with labelling fields Differentiation characteristic 3 - Sales with integral bus coupling unit Safety Protection with dismantling protection **Use conditions** -5...45 °C Operating temperature Identification Application, usage KNX - operating systems Product family product family: push-button Main design line KNX - Berker Q.1/Q.3 Secondary design line(s) Berker Q.3; Berker Q.7; Berker Q.1 Instructions

Labelling field sheet, order no. 9498 31 03, available

separately.

Information text