



75144329



IP20



## Technical characteristics

### Functions

With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions
Light scenes	retrieval, adjustment and storage of 8 light scenes

### Compatibility

Extension unit	extension unit for light scene push-button
----------------	--------------------------------------------

### Controls and indicators

With LED indication	Yes
Number of buttons	4
Operation	one push-button operation for switching, pushing, shutters and dimming

### Dimensions

Labelling field length (W x H)	56.4 x 12 mm
Height	71 mm
Width	71 mm

### Measurement

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
-------------------	-----------------------------------------------------------------------------------------

### Screen

With display	No
--------------	----

### Materials

Colour of labelling	105,105,105
Colour of design line	polar white
RAL colour	RAL 9010 - Pure white
Material for printing	Paper
Surface appearance	velvety
Type of surface treatment	untreated
Material family	Plastic

### LED control

LED	with white operation LED and 8 amber status LEDs
-----	--------------------------------------------------

### Settings

Supported configuration modes	system
Parameterisation	single and two push-button operation parameterisable

**Scope of delivery**

Bus connection included	Yes
-------------------------	-----

**Equipment**

Number of actuation points	8
----------------------------	---

With anti-theft/dismantling protection	Yes
----------------------------------------	-----

Type of configuration	Beschriftungsfeld(er) - Folie
-----------------------	-------------------------------

Product type:	product type: push-button 4gang
---------------	---------------------------------

Controller extension unit	usable as thermostat extension unit
---------------------------	-------------------------------------

**Use**

Differentiation characteristic 1 - Sales	with labelling fields
------------------------------------------	-----------------------

Differentiation characteristic 3 - Sales	with integral bus coupling unit
------------------------------------------	---------------------------------

**Safety**

Protection	with dismantling protection
------------	-----------------------------

**Use conditions**

Operating temperature	-5...45 °C
-----------------------	------------

**Identification**

Application, usage	KNX - operating systems
--------------------	-------------------------

Product family	product family: push-button
----------------	-----------------------------

Main design line	KNX - Berker Q.1/Q.3
------------------	----------------------

Secondary design line(s)	Berker Q.3 ; Berker Q.7 ; Berker Q.1
--------------------------	--------------------------------------

**Instructions**

Information text	Labelling field sheet, order no. 9498 32 04, available separately.
------------------	--------------------------------------------------------------------