




75144860

IP20



Touch sensor, 4-gang comf, intg bus coupling unit, KNX - R.1, glass p. white

Technical characteristics

Architecture

Fixing mode flush-mounting

Functions

With room temperature controller Yes

Function for switch, push-button, dimmer and shutter functions ; Blocking function for sensor surface e.g. for cleaning the glass surface

Compatibility

Extension unit extension unit for light scene push-button

Controls and indicators

With LED indication Yes

Number of buttons 0

Operation operation by gently touching the sensor surfaces on the white LED

Dimensions

Depth 23 mm

Height 152 mm

Width 81 mm

Power

Current consumption 12.5 mA

Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display Yes

Materials

Colour of design line glass polar white

Colour polarwhite

RAL colour RAL 9010 - Pure white

Material glass

Surface appearance glossy

Type of surface treatment untreated

LED control

LED with blue operation LED and 8 white status LEDs

Installation, mounting		
Installation mode	for vertical mounting	
Connection		
Bus coupling unit	with integral bus coupling unit	
Bus connection	bus connection via connecting terminal	
Scope of delivery		
Bus connection included	Yes	
Accessories included		
Matching products	for additional products to complement the installation in matching colours/materials, refer to the Design platform R.1/R.3 ; for suitable frames in the same "style" for additional applications, see the Design line R.x	
Equipment		
Number of actuation points	8	
With anti-theft/dismantling protection	Yes	
Use		
Differentiation characteristic 3 - Sales	with integral bus coupling unit	
Safety		
Protection index IP	IP20	
REACH conform	Yes	
RoHS conform	Yes	
Use conditions		
Operating temperature	-5...45 °C	
Temperature	temperature measurement via internal temperature sensor or external communication object ; integrated temperature sensor for operation as controller extension unit ; additional connection for external temperature sensor	
Identification		
Application, usage	KNX - operating systems	
Main design line	KNX - Berker R.1	
Secondary design line(s)	KNX ; Berker R.1	