



75161594

IP20

**B.IQ push-button 1gang comf, KNX - B.IQ, al., al. anodised**

**Technical characteristics**

**Architecture**

Fixing mode flush-mounting

**Functions**

With room temperature controller No

Function for switch, push-button, dimmer and shutter functions

**Compatibility**

Extension unit extension unit for light scene push-button

**Controls and indicators**

With LED indication Yes

Number of buttons 1

Operation activation of second user level via object, one push-button operation for switching, pushing, shutters and dimming

**Dimensions**

Assembling height 16.7 mm

Height 88.5 mm

Width 88.5 mm

**Measurement**

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

**Screen**

With display No

**Materials**

Colour of design line Aluminium

Colour aluminium

RAL colour RAL 9006 - White aluminium

Material / workmanship aluminium, anodised

Material Aluminium

Surface appearance matt

Type of surface treatment Anodised

**LED control**

LED with blue operation LED and 2 white status LEDs (labelling field illumination)

**Connection**

---

Bus coupling unit	for bus coupling unit flush-mounted
-------------------	-------------------------------------

---

**Settings**

---

Supported configuration modes	system, PB
-------------------------------	------------

---

Parameterisation	single and two push-button operation parameterisable
------------------	---

**Scope of delivery**

---

Bus connection included	No
-------------------------	----

---

**Accessories included**

---

Box	for installation in single standard wall boxes
-----	--

---

Matching products	for aluminium frames in the same "style" for additional applications, see the Design line B.7, for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x
-------------------	---

**Equipment**

---

Number of actuation points	2
----------------------------	---

---

With anti-theft/dismantling protection	Yes
--	-----

---

Product type:	product type: B.IQ
---------------	--------------------

**Safety**

---

Protection index IP	IP20
---------------------	------

---

Protection	with dismantling protection
------------	-----------------------------

---

Alarm	alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte
-------	---

**Use conditions**

---

Operating temperature	-5...45 °C
-----------------------	------------

---

**Identification**

---

Application, usage	KNX - operating systems
--------------------	-------------------------

---

Product family	product family: push-button
----------------	-----------------------------

---

Main design line	KNX - Berker B.IQ
------------------	-------------------

---

Secondary design line(s)	KNX, Berker B.IQ
--------------------------	------------------

---