



75161599



IP20

B.IQ push-button 1gang comf, KNX - B.IQ, p. white, matt, plastic

Technical characteristics

Functions

| | |
|----------------------------------|----|
| With room temperature controller | No |
|----------------------------------|----|

| | |
|----------|---|
| Function | for switch, push-button, dimmer and shutter functions |
|----------|---|

Compatibility

| | |
|----------------|--|
| Extension unit | extension unit for light scene push-button |
|----------------|--|

Controls and indicators

| | |
|---------------------|-----|
| With LED indication | Yes |
|---------------------|-----|

| | |
|-------------------|---|
| Number of buttons | 1 |
|-------------------|---|

| | |
|-----------|---|
| Operation | activation of second user level via object ; one push-button operation for switching, pushing, shutters and dimming |
|-----------|---|

Dimensions

| | |
|--------|---------|
| Height | 88.5 mm |
|--------|---------|

| | |
|-------|---------|
| Width | 88.5 mm |
|-------|---------|

Measurement

| | |
|-------------------|---|
| Value transmitter | value transmitter for dimming, position, brightness and temperature values 1 and 2 byte |
|-------------------|---|

Screen

| | |
|--------------|----|
| With display | No |
|--------------|----|

Materials

| | |
|---------------------|-------------|
| Colour of labelling | 105,105,105 |
|---------------------|-------------|

| | |
|-----------------------|-------------|
| Colour of design line | polar white |
|-----------------------|-------------|

| | |
|------------|-----------------------|
| RAL colour | RAL 9010 - Pure white |
|------------|-----------------------|

| | |
|--------------------|------|
| Surface appearance | matt |
|--------------------|------|

| | |
|---------------------------|-----------|
| Type of surface treatment | untreated |
|---------------------------|-----------|

LED control

| | |
|-----|--|
| LED | with blue operation LED and 2 white status LEDs (labelling field illumination) |
|-----|--|

Connection

| | |
|-------------------|-------------------------------------|
| Bus coupling unit | for bus coupling unit flush-mounted |
|-------------------|-------------------------------------|

Settings

| | |
|-------------------------------|------------|
| Supported configuration modes | system, PB |
|-------------------------------|------------|

| | |
|------------------|--|
| Parameterisation | single and two push-button operation parameterisable |
|------------------|--|

Scope of delivery

| | |
|-------------------------|----|
| Bus connection included | No |
|-------------------------|----|

Accessories included

| | |
|-----|--|
| Box | for installation in single standard wall boxes |
|-----|--|

| | |
|-------------------|--|
| Matching products | for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x ; for plastic frames in the same "style" for additional applications, see the Design line B.7 |
|-------------------|--|

Equipment

| | |
|----------------------------|---|
| Number of actuation points | 2 |
|----------------------------|---|

| | |
|--|-----|
| With anti-theft/dismantling protection | Yes |
|--|-----|

| | |
|-----------------------|------------|
| Type of configuration | Laserdruck |
|-----------------------|------------|

| | |
|---------------|--------------------|
| Product type: | product type: B.IQ |
|---------------|--------------------|

Safety

| | |
|---------------|-----|
| REACH conform | Yes |
|---------------|-----|

| | |
|--------------|-----|
| RoHS conform | Yes |
|--------------|-----|

| | |
|------------|-----------------------------|
| Protection | with dismantling protection |
|------------|-----------------------------|

| | |
|-------|---|
| Alarm | alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte |
|-------|---|

Use conditions

| | |
|-----------------------|------------|
| Operating temperature | -5...45 °C |
|-----------------------|------------|

Identification

| | |
|--------------------|-------------------------|
| Application, usage | KNX - operating systems |
|--------------------|-------------------------|

| | |
|----------------|-----------------------------|
| Product family | product family: push-button |
|----------------|-----------------------------|

| | |
|------------------|-------------------|
| Main design line | KNX - Berker B.IQ |
|------------------|-------------------|

| | |
|--------------------------|-------------------|
| Secondary design line(s) | KNX ; Berker B.IQ |
|--------------------------|-------------------|