



75161770









Technical characteristics

u			

With room temperature controller		No		
	Function	for switch, push-button, dimmer and shutter functions		

Compatibility

Extension unit extension unit for light scene push-button

Controls and indicators

With LED indication	Yes
Number of buttons	1

one push-button operation for switching, pushing, shutters and dimming ; activation of second user level via object

Dimensions

Operation

Labelling field length (W x H)	66.8 x 52.8 mm
Height	52.8 mm
Width	66.8 mm

Measurement

value transmitter for dimming, position, brightness Value transmitter and temperature values 1 and 2 byte

Screen

With display No

Materials

Colour of labelling	105,105,105
Colour of design line	polar white
Colour independent of design lines	polar white
RAL colour	RAL 9010 - Pure white
Material for printing	Paper
Surface appearance	glossy
Type of surface treatment	untreated
Material family	Plastic

LED control

LED with white operation LED and 2 red status LEDs

Connection

Bus coupling unit for bus coupling unit flush-mounted

Settings	
Parameterisation	single and two push-button operation parameterisable
Scope of delivery	
Bus connection included	No
Equipment	
Number of actuation points	2
With anti-theft/dismantling protection	Yes
Type of configuration	Beschriftungsfeld(er) - Folie
Product type:	product type: push-button 1gang
Use	
Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 3 - Sales	with horizontal operation
Safety	
Protection	with dismantling protection
Alarm	alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-buttor
Secondary design line(s)	Berker K.1 ; KNX