


75161770



Technical characteristics

Functions

With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions

Compatibility

Extension unit	extension unit for light scene push-button
----------------	--

Controls and indicators

With LED indication	Yes
Number of buttons	1
Operation	one push-button operation for switching, pushing, shutters and dimming ; activation of second user level via object

Dimensions

Labelling field length (W x H)	66.8 x 52.8 mm
Height	52.8 mm
Width	66.8 mm

Measurement

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
-------------------	---

Screen

With display	No
--------------	----

Materials

Colour of labelling	105,105,105
Colour of design line	polar white
Colour independent of design lines	polar white
RAL colour	RAL 9010 - Pure white
Material for printing	Paper
Surface appearance	glossy
Type of surface treatment	untreated
Material family	Plastic

LED control

LED	with white operation LED and 2 red status LEDs
-----	--

Connection

Bus coupling unit	for bus coupling unit flush-mounted
-------------------	-------------------------------------

Settings

Parameterisation single and two push-button operation
parameterisable

Scope of delivery

Bus connection included No

Equipment

Number of actuation points 2

With anti-theft/dismantling protection Yes

Type of configuration Beschriftungsfeld(er) - Folie

Product type: product type: push-button 1gang

Use

Differentiation characteristic 1 - Sales with labelling field

Differentiation characteristic 3 - Sales with horizontal operation

Safety

Protection with dismantling protection

Alarm alarm telegram after disconnection from bus
coupling unit 1 bit or 1 byte

Use conditions

Operating temperature -5...45 °C

Identification

Application, usage KNX - operating systems

Product family product family: push-button

Secondary design line(s) Berker K.1 ; KNX