



75161780





Berker S.1/B.3/B.7 Push Button 1-gang, Comfort with Label, White and Polar White

Technical characteristics

Fixing mode	flush-mounting
Functions	
With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions
Compatibility	
Extension unit	extension unit for light scene push-button
Controls and indicators	
With LED indication	Yes
Number of buttons	1
Operation	activation of second user level via object, one push- button operation for switching, pushing, shutters and dimming
Dimensions	
Labelling field length (W x H)	52.3 mm
Height	55.5 mm
Width	55.4 mm
Measurement	
Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
Screen	
With display	No
Materials	
Colour of design line	white/polar white
Colour independent of design lines	for white and polar white
Colour	white/polarwhite
RAL colour	RAL 1013 - Oyster white
Material	thermoplastic
Material for printing	Paper
Type of surface treatment	untreated
Material family	Plastic
LED control	

with white operation LED and 2 red status LEDs

LED

Connection	
Bus coupling unit	for bus coupling unit flush-mounted
Settings	
Parameterisation	single and two push-button operation parameterisable
Scope of delivery	
Bus connection included	No
Equipment	
Number of actuation points	2
With anti-theft/dismantling protection	Yes
Type of configuration	Beschriftungsfeld(er) - Folie
Product type:	product type: push-button 1gang
Use	
Differentiation characteristic 1 - Sales	with labelling field
Differentiation characteristic 3 - Sales	with horizontal operation
Safety	
Protection index IP	IP20
Protection	with dismantling protection
Alarm	alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte
Use conditions	
Operating temperature	-545 °C
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button

KNX, Berker S.1, Berker B.3, Berker B.7

Secondary design line(s)