


75161780



IP20



## Berker S.1/B.3/B.7 Push Button 1-gang, Comfort with Label, White and Polar White

### Technical characteristics

#### Functions

With room temperature controller No

Function for switch, push-button, dimmer and shutter functions

#### Compatibility

Extension unit extension unit for light scene push-button

#### Controls and indicators

With LED indication Yes

Number of buttons 1

Operation activation of second user level via object ; one push-button operation for switching, pushing, shutters and dimming

#### Dimensions

Labelling field length (W x H) 52.3 mm

Height 55.5 mm

Width 55.4 mm

#### Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

#### Screen

With display No

#### Materials

Colour of labelling 105,105,105

Colour of design line white/polar white

Colour independent of design lines for white and polar white

Material for printing Paper

Surface appearance glossy

Type of surface treatment untreated

Material family Plastic

#### LED control

LED with white operation LED and 2 red status LEDs

#### Connection

Bus coupling unit for bus coupling unit flush-mounted

#### Settings

**Scope of delivery**

Bus connection included	No
-------------------------	----

**Equipment**

Number of actuation points	2
----------------------------	---

With anti-theft/dismantling protection	Yes
--	-----

Type of configuration	Beschriftungsfeld(er) - Folie
-----------------------	-------------------------------

Product type:	product type: push-button 1gang
---------------	---------------------------------

**Use**

Differentiation characteristic 1 - Sales	with labelling field
--	----------------------

Differentiation characteristic 3 - Sales	with horizontal operation
--	---------------------------

**Safety**

Protection	with dismantling protection
------------	-----------------------------

Alarm	alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte
-------	--

**Use conditions**

Operating temperature	-5...45 °C
-----------------------	------------

**Identification**

Application, usage	KNX - operating systems
--------------------	-------------------------

Product family	product family: push-button
----------------	-----------------------------

Secondary design line(s)	KNX ; Berker S.1 ; Berker B.3 ; Berker B.7
--------------------------	--