

Yes

217,217,217



75161785









Berker S.1/B.3/B.7 Push Button 1-gang, Comfort with Label, Anthracite/Aluminium

Technical characteristics

F				

With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions

Compatibility

Extension unit	extension unit for light scene push-button

Controls and indicators

With LED indication

Number of buttons	1
	one push-button operation for switching, pushing,

shutters and dimming; activation of second user level via object

Dimensions

Operation

Labelling field length (W x H)	52.3 mm
Height	55.5 mm
Width	55.4 mm

Measurement

	value transmitter for dimming, position, brightness
Value transmitter	and temperature values 1 and 2 byte

Screen

With display	No
--------------	----

Materials

Colour of labelling

Colour of design line	aluminium/anthracite	
Colour independent of design lines	for anthracite and aluminium	
Material for printing	Paper	
Surface appearance	glossy	

Type of surface treatment untreated

Material family Plastic

LED control

LED	with white operation LED and 2 red status LEDs

Connection

Bus coupling unit for bus coupling unit flush-mounted

Settings

Scope of delivery

Bus connection included No

Equipment

Number of actuation points 2

With anti-theft/dismantling protection Yes

Type of configuration Beschriftungsfeld(er) - Folie

Product type: product type: push-button 1gang

Use

Differentiation characteristic 1 - Sales with labelling field

Differentiation characteristic 3 - Sales with horizontal operation

Safety

Protection with dismantling protection

alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

Use conditions

Operating temperature -5...45 °C

Identification

Application, usage

KNX - operating systems

Product family

product family: push-button

Secondary design line(s)

KNX; Berker S.1; Berker B.3; Berker B.7