



75162370



Technical characteristics

Anal the shows	
Architecture Fixing mode	flush-mounting
Functions	
With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions
Compatibility	
Extension unit	extension unit for light scene push-button
Controls and indicators	
With LED indication	Yes
Number of buttons	2
Dimensions	
Labelling field length (W x H)	66.8 x 25 mm
Height	55.1 mm
Width	70.5 mm
Measurement	
Value transmitter	dimming / position value transmitter 1 byte
Screen	
With display	No
Materials	
Colour of design line	polar white
Colour	polarwhite
RAL colour	RAL 9010 - Pure white
Material	Plastic/metal
Material for printing	Paper
Type of surface treatment	untreated
Material family	Plastic
LED control	
LED - KNX	with white operation LED and 4 red status LEDs
Connection	
Bus coupling unit	for bus coupling unit flush-mounted

Scope of delivery

Bus connection included No **Equipment** Number of actuation points 4 With anti-theft/dismantling protection Yes Type of configuration Beschriftungsfeld(er) - Folie Product type: product type: push-button 2gang Use Differentiation characteristic 1 - Sales with labelling fields Differentiation characteristic 3 - Sales with horizontal operation Safety Protection index IP IP20 Protection with dismantling protection **Use conditions** -5...45 °C Operating temperature Identification KNX - operating systems, Radio bus - operating Application, usage systems

product family: push-button

KNX, Radio bus, Berker K.1

Product family

Secondary design line(s)