



75163093

**IP20**

**B.IQ push-button 3gang, KNX - B.IQ, stainless steel, metal brushed**

**Technical characteristics**

**Architecture**

Fixing mode flush-mounting

**Functions**

With room temperature controller No

Function for switch, push-button, dimmer and shutter functions

**Compatibility**

Extension unit extension unit for light scene push-button

**Controls and indicators**

With LED indication Yes

Number of buttons 3

**Dimensions**

Assembling height 16.7 mm

Height 88.5 mm

Width 88.5 mm

**Measurement**

Value transmitter dimming / position value transmitter 1 byte

**Screen**

With display No

**Materials**

Colour of design line Stainless steel

Colour stainless steel

RAL colour RAL 9022 - Pearl light grey

Material / workmanship metal brushed

Material stainless steel

Surface appearance matt

Type of surface treatment brushed

Material family Metal

**LED control**

LED with blue operation LED and 6 white status LEDs (labelling field illumination)

**Connection**

Bus coupling unit for bus coupling unit flush-mounted

|  |   |
|--|---|
| <b>Scope of delivery</b>               |   |
| Bus connection included                | No  |
| <b>Accessories included</b>            |   |
| Box                                    | for installation in single standard wall boxes  |
| Matching products                      | for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x, for stainless steel frames in the same "style" for additional applications, see the Design line B.7 |
| <b>Equipment</b>                       |   |
| Number of actuation points             | 6   |
| With anti-theft/dismantling protection | Yes   |
| Product type:                          | product type: B.IQ  |
| <b>Safety</b>                          |   |
| Protection index IP                    | IP20  |
| REACH conform                          | Yes   |
| RoHS conform                           | Yes   |
| Protection                             | with dismantling protection   |
| <b>Use conditions</b>                  |   |
| Operating temperature                  | -5...45 °C  |
| <b>Identification</b>                  |   |
| Application, usage                     | KNX - operating systems   |
| Product family                         | product family: push-button   |
| Main design line                       | KNX - Berker B.IQ   |
| Secondary design line(s)               | Berker B.IQ, KNX  |