



75163375



Technical characteristics

Architecture	
Fixing mode	flush-mounting
Functions	
With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions
Compatibility	
Extension unit	extension unit for light scene push-button
Controls and indicators	
With LED indication	Yes
Number of buttons	3
Dimensions	
Labelling field length (W x H)	66.8 x 15.7 mm
Height	55.1 mm
Width	70.5 mm
Measurement	
Value transmitter	dimming / position value transmitter 1 byte
Screen	
With display	No
Materials	
Colour of labelling	217,217,217
Colour of design line	anthracite
Colour	anthracite
RAL colour	RAL 7021 - Black grey
Material	Plastic/metal
Material for printing	Paper
Surface appearance	matt
Type of surface treatment	Painted
Material family	Plastic
LED control	
LED - KNX	with white operation LED and 6 red status LEDs
Connection	
Bus coupling unit	for bus coupling unit flush-mounted

No
6
Yes
Beschriftungsfeld(er) - Folie
product type: push-button 3gang
with labelling fields
with horizontal operation
IP20
with dismantling protection
-545 °C
KNX - operating systems
product family: push-button
KNX - Berker K.1

Berker K.1, KNX

Secondary design line(s)