



75164590





B.IQ push-button 4gang comf, KNX - B.IQ, glass p. white

Technical characteristics

Functions	
With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions
Compatibility	
Extension unit	extension unit for light scene push-button
Controls and indicators	
With LED indication	Yes
Number of buttons	4

second operating level via object or 3-button handle ; lockable via 3-button actuation ; one push-button operation for switching, pushing, shutters and dimming

Dimensions

Operation

Assembling height	16.7 mm
Height	118.1 mm
Width	88.5 mm

Measurement

	value transmitter for dimming, position, brightness
Value transmitter	and temperature values 1 and 2 byte

Screen

With display	No
--------------	----

Materials

Colour of design line	glass polar white
RAL colour	RAL 9010 - Pure white
Surface appearance	glossy

LED control

	with blue operation LED and 8 white status LEDs
LED	(labelling field illumination)

Connection

Bus coupling unit for bus coupling unit flush-mounted

Settings

Supported configuration modes system, P
Supported configuration modes system, P

single and two push-button operation Parameterisation parameterisable

Scope of delivery	
Bus connection included	No
Accessories included	
Box	for installation in single standard wall boxes
Matching products	for glass frames in the same "style" for additional applications, see the Design line B.7; for additional products to complement the installation in matching colours/materials, refer to the Design platform 5.1/B.x
matering produces	3.175.7
Equipment	
Number of actuation points	8
With anti-theft/dismantling protection	Yes
Product type:	product type: B.IQ
Safety	
REACH conform	Yes
RoHS conform	Yes
Protection	with dismantling protection
Alarm	alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte
Use conditions	
Operating temperature	-545 °C
Identification	