

105,105,105











#### **Technical characteristics**

-			_ :		-		_
-	u	n	C	CI	О	n	ıs

With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions

# Compatibility

Extension unit extension unit for light scene push-button

#### **Controls and indicators**

With LED indication	Yes
Number of buttons	4

second operating level via object or 3-button handle ; one push-button operation for switching, pushing, shutters and dimming; lockable via 3-button

#### **Dimensions**

Operation

Labelling field length (W x H)	66.8 x 25 mm
Height	111.1 mm
Width	70.5 mm

#### Measurement

	value transmitter for dimming, position, brightness
Value transmitter	and temperature values 1 and 2 byte

# Screen

With display	No
--------------	----

# Materials

Colour of labelling

Colour of design line	polar white
RAL colour	RAL 9010 - Pure white
Material for printing	Paper
Surface appearance	glossy

Type of surface treatment untreated

Material family Plastic

# LED control

LED with white operation LED and 8 red status LEDs

# Connection

Bus coupling unit for bus coupling unit flush-mounted

## **Settings**

## Scope of delivery

Bus connection included No

## **Equipment**

Number of actuation points 8

With anti-theft/dismantling protection Yes

Type of configuration Beschriftungsfeld(er) - Folie

Product type: product type: push-button 4gang

#### Use

Differentiation characteristic 1 - Sales with labelling fields

Differentiation characteristic 3 - Sales with horizontal operation

#### Safety

Protection with dismantling protection

alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

## **Use conditions**

Operating temperature -5...45 °C -20...70 °C (storage at > 45°C reduces the service Storage/transport temperature

## Identification

Application, usage KNX - operating systems

Product family product family: push-button

Secondary design line(s) Berker K.1; KNX

#### Instructions

 $\begin{tabular}{lll} \begin{tabular}{lll} \begin{$