

Plastic











#### **Technical characteristics**

_						
E	111	nc	*1	0	n	c

With room temperature controller	No
Function	for switch, push-button, dimmer and shutter functions

# Compatibility

Extension unit extension unit for light scene push-button

### **Controls and indicators**

With LED indication	Yes
Number of buttons	4

lockable via 3-button actuation; second operating level via object or 3-button handle; one push-button operation for switching, pushing, shutters and

# Dimensions

Operation

Labelling field length (W x H)	66.8 x 25 mm
Height	111.1 mm
Width	70.5 mm

#### Measurement

	value transmitter for dimming, position, brig	ntness
Value transmitter	and temperature values 1 and	2 byte

## Screen

With display	No

#### Materials

Colour of labelling	217,217,217
Colour of design line	anthracite
Material for printing	Paper
Surface appearance	glossy
Type of surface treatment	untreated

## LED control

Material family

LFD	with white operation LED and 8 red status LEDs

# Connection

Bus coupling unit for bus coupling unit flush-mounted

### **Settings**

Parameterisation	single and two push-button operation parameterisable
Scope of delivery	
Bus connection included	No
Equipment	
Number of actuation points	8
With anti-theft/dismantling protection	Yes
Type of configuration	Beschriftungsfeld(er) - Folie
Product type:	product type: push-button 4gang
Use	
Differentiation characteristic 1 - Sales	with labelling fields
Differentiation characteristic 3 - Sales	with horizontal operation
Safety	
Protection	with dismantling protection
Alarm	alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte
Use conditions	
Operating temperature	-545 °C
Storage/transport temperature	-2070 °C (storage at > 45°C reduces the service life)
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker K.1
Secondary design line(s)	Berker K.1 ; KNX
Instructions	

Use only in combination with frame frame with large  $$\operatorname{cut}$$  out.