


75164775



Technical characteristics

Functions

With room temperature controller	No
----------------------------------	----

Function	for switch, push-button, dimmer and shutter functions
----------	---

Compatibility

Extension unit	extension unit for light scene push-button
----------------	--

Controls and indicators

With LED indication	Yes
---------------------	-----

Number of buttons	4
-------------------	---

Operation	lockable via 3-button actuation ; second operating level via object or 3-button handle ; one push-button operation for switching, pushing, shutters and dimming
-----------	---

Dimensions

Labelling field length (W x H)	66.8 x 25 mm
--------------------------------	--------------

Height	111.1 mm
--------	----------

Width	70.5 mm
-------	---------

Measurement

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
-------------------	---

Screen

With display	No
--------------	----

Materials

Colour of labelling	217,217,217
---------------------	-------------

Colour of design line	anthracite
-----------------------	------------

Material for printing	Paper
-----------------------	-------

Surface appearance	glossy
--------------------	--------

Type of surface treatment	untreated
---------------------------	-----------

Material family	Plastic
-----------------	---------

LED control

LED	with white operation LED and 8 red status LEDs
-----	--

Connection

Bus coupling unit	for bus coupling unit flush-mounted
-------------------	-------------------------------------

Settings

Parameterisation

single and two push-button operation
parameterisable

Scope of delivery

Bus connection included No

Equipment

Number of actuation points 8

With anti-theft/dismantling protection Yes

Type of configuration Beschriftungsfeld(er) - Folie

Product type: product type: push-button 4gang

Use

Differentiation characteristic 1 - Sales with labelling fields

Differentiation characteristic 3 - Sales with horizontal operation

Safety

Protection with dismantling protection

Alarm alarm telegram after disconnection from bus
coupling unit 1 bit or 1 byte

Use conditions

Operating temperature -5...45 °C

Storage/transport temperature -20...70 °C (storage at > 45°C reduces the service
life)

Identification

Application, usage KNX - operating systems

Product family product family: push-button

Main design line KNX - Berker K.1

Secondary design line(s) Berker K.1 ; KNX

Instructions

Special note text Use only in combination with frame frame with large
cut-out.