




75261185



KNX cont. 1.1 m, KNX - B.3/B.7, ant., matt

Technical characteristics

Functions

Function	parameter defineable lock function
----------	------------------------------------

Compatibility

Extension unit	also suitable as extension unit
----------------	---------------------------------

Controls and indicators

Number of switching segments	72
------------------------------	----

Dimensions

Dimensions assembling height	23.5 mm
------------------------------	---------

Nominal mounting height	1.1 m
-------------------------	-------

Measurement

Detection field, semi-oval shaped	≈ 10 x 12 m
-----------------------------------	-------------

Reach distance

Range, frontal	≈ 10 m
----------------	--------

Range, side	each ≈ 6 m
-------------	------------

Cover, door

Cover	with cover to limit detection angle to 90°
-------	--

Detection

Number of detection levels	2
----------------------------	---

Detection angle	180 °
-----------------	-------

Sensor type	detector of movement
-------------	----------------------

Materials

Colour of design line	anthracite
-----------------------	------------

RAL colour	RAL 7021 - Black grey
------------	-----------------------

Material	thermoplastic
----------	---------------

Surface appearance	matt
--------------------	------

Lighting control

Response brightness, configurable	1...1000 lx / daytime operation
-----------------------------------	---------------------------------

Connection

Bus coupling unit	for bus coupling unit flush-mounted
-------------------	-------------------------------------

Settings

Supported configuration modes	system
-------------------------------	--------

Response sensitivity, settable	20...100 %
Delay time	≈ 10 s
Additional delay time programmable	130...152 ms
Setting	with potentiometer for fine adjustment of the response sensitivity
Equipment	
Product type:	product type: movement
Use conditions	
Operating temperature	-5...45 °C
Identification	
Application, usage	KNX - sensors
Product family	product family: physical sensors
Main design line	KNX - Berker S.1/B.3/B.7
Secondary design line(s)	Berker B.7, Motion detector, KNX, Berker B.3
Instructions	
Information text	Continuous direct sunlight penetrating the upward-pointing detection plane can result in failure of the motion detector. Only suitable for indoor areas!