



75662773



Push-button 2gang with room thermostat, display, K.5, stainless steel

Technical characteristics

Architecture

Fixing mode flush-mounting

Functions

With room temperature controller Yes

Timers with room temperature timer

Compatibility

Extension unit extension unit for light scene push-button

Controls and indicators

With LED indication Yes

Number of buttons 2

Operation one push-button operation for switching, pushing, shutters and dimming

Dimensions

Labelling field length (W x H) 66.8 x 15.7 mm

Height 55.1 mm

Width 70.9 mm

Measurement

Value transmitter value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Screen

With display Yes

Materials

Colour of design line stainless steel

Colour stainless steel

RAL colour RAL 9022 - Pearl light grey

Material thermoplastic

Material for printing Paper

Surface appearance matt

Type of surface treatment Painted

Material family Plastic

LED control

LED with white operation LED and 4 red status LEDs

Connection

Settings

| | |
|------------------|---------------------------------------------------------|
| Parameterisation | single and two push-button operation parameterisable |
|------------------|---------------------------------------------------------|

Scope of delivery

| | |
|-------------------------|----|
| Bus connection included | No |
|-------------------------|----|

Accessories included

| | |
|-----|------------------------------------------------|
| Box | for installation in single standard wall boxes |
|-----|------------------------------------------------|

Equipment

| | |
|----------------------------------------|------------------------------------------------|
| Number of actuation points | 6 |
| With anti-theft/dismantling protection | Yes |
| Type of configuration | Beschriftungsfeld(er) - Folie |
| Product type: | product type: push-button 2gang |
| Control | for individual single room temperature control |

Software

| | |
|--------|----------------------------------|
| Update | with flash-controller technology |
|--------|----------------------------------|

Safety

| | |
|---------------------|------------------------------------------------------------------------------|
| Protection index IP | IP20 |
| Protection | with dismantling protection |
| Alarm | alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte |

Use conditions

| | |
|-------------------------|------------|
| Operating temperature | -5...45 °C |
| Energy efficiency class | IV (2%) |

Identification

| | |
|--------------------------|-----------------------------|
| Application, usage | KNX - operating systems |
| Product family | product family: push-button |
| Main design line | KNX - Berker K.1/K.5 |
| Secondary design line(s) | KNX, Berker K.5 |