



75663726



**Push-butt. 3gang, w. lab. fields, room therm., displ., Q.x, anthr. velvety**

**Technical characteristics**

**Functions**

With room temperature controller	Yes
Function	for switch, push-button, dimmer, blind and thermostat functions ; with valve protection function
Light scenes	retrieval, adjustment and storage of 8 light scenes
Timers	with room temperature timer
Operating mode	controller operating modes: comfort, standby, night and frost/heat protection mode

**Compatibility**

Extension unit	extension unit for light scene push-button
----------------	--

**Controls and indicators**

With LED indication	Yes
Dimming	area dimming
Number of buttons	3
Operation	one push-button operation for switching, pushing, shutters and dimming ; blind operating concepts short-long-short and long-short parameterisable
Indication / display	LC display with symbol display ; display of operating mode, controller lockout, room/outside temperature, time (clock required)
Button / push-button	with 2 additional display buttons

**Connectivity**

Encoding	with button blocking function
----------	-------------------------------

**Dimensions**

Labelling field length (W x H)	56.4 x 26.8 mm
Height	123.2 mm
Width	70.8 mm

**Measurement**

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
-------------------	---

**Screen**

With display	Yes
--------------	-----

**Materials**

Colour of labelling	217,217,217
Colour of design line	anthracite
Material for printing	Paper

Surface appearance	velvety
Material family	Plastic
<b>LED control</b>	
LED	with white operation LED and 6 amber status LEDs
<b>Settings</b>	
Supported configuration modes	system
Parameterisation	single and two push-button operation parameterisable ; presence button parameterisable to extend comfort ; end customer display scope parameterisable
Programming	programmable from ETS2, V1.2a
<b>Scope of delivery</b>	
Bus connection included	Yes
<b>Equipment</b>	
Number of actuation points	8
With anti-theft/dismantling protection	Yes
Type of configuration	Beschriftungsfeld(er) - Folie
Product type:	product type: push-button 3gang
Heating	for heating and/or cooling mode with/without auxiliary step
Control	for individual single room temperature control ; for continuous (PI) or switched (2-point) control of max. 2 control circuits ; control parameter for heating / cooling unit pre-set
<b>Use</b>	
Differentiation characteristic 1 - Sales	with labelling fields
Differentiation characteristic 2 - Sales	Display
Differentiation characteristic 3 - Sales	integrated bus coupling unit
<b>Software</b>	
Update	with flash-controller technology
<b>Safety</b>	
REACH conform	Yes
RoHS conform	Yes
Halogen free	No
Protection	with dismantling protection
Alarm	alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte
<b>Use conditions</b>	
Operating temperature	-5...45 °C
Temperature	temperature measurement via internal and/or external sensor with mean value formation
Energy efficiency class	IV (2%)
<b>Identification</b>	
Application, usage	KNX - operating systems
Product family	product family: push-button

Subject to technical modifications

Main design line

KNX - Berker Q.1/Q.3

Secondary design line(s)

KNX ; Berker Q.1 ; Berker Q.3 ; Berker Q.7 ; Berker  
Q.9

---

**Instructions**

Special note text

Use only in combination with frame frame with large  
cut-out.

Information text

Labelling field sheet, order no. 9498 30 02, available  
separately.