



75663773



## Push-button 3gang with room thermostat, display, K.5, stainless steel

### Technical characteristics

#### Functions

With room temperature controller	Yes
Function	with valve protection function ; for switch, push-button, dimmer, blind and thermostat functions
Timers	with room temperature timer
Operating mode	controller operating modes: comfort, standby, night and frost/heat protection mode

#### Compatibility

Extension unit	extension unit for light scene push-button
----------------	--

#### Controls and indicators

With LED indication	Yes
Dimming	area dimming
Number of buttons	3
Operation	one push-button operation for switching, pushing, shutters and dimming ; blind operating concepts short-long-short and long-short parameterisable
Indication / display	LC display with symbol display ; display of operating mode, controller lockout, room/outside temperature, time (clock required)
Button / push-button	with 2 additional display buttons

#### Connectivity

Encoding	with button blocking function
----------	-------------------------------

#### Dimensions

Labelling field length (W x H)	66.8 x 24.9 mm
Height	111.1 mm
Width	70.9 mm

#### Measurement

Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
-------------------	---

#### Screen

With display	Yes
--------------	-----

#### Materials

Colour of labelling	105,105,105
Colour of design line	stainless steel
Material for printing	Paper
Surface appearance	matt

Type of surface treatment

untreated

### LED control

LED with white operation LED and 6 red status LEDs

### Connection

Bus coupling unit for bus coupling unit flush-mounted

### Settings

Parameterisation single and two push-button operation parameterisable ; presence button parameterisable to extend comfort ; end customer display scope parameterisable

Programming programmable from ETS2, V1.2a

### Scope of delivery

Bus connection included No

### Equipment

Number of actuation points 8

With anti-theft/dismantling protection Yes

Type of configuration Beschriftungsfeld(er) - Folie

Product type: product type: push-button 3gang

Heating for heating and/or cooling mode with/without auxiliary step

Control for continuous (PI) or switched (2-point) control of max. 2 control circuits ; control parameter for heating / cooling unit pre-set ; for individual single room temperature control

### Use

Differentiation characteristic 1 - Sales Labelling fields

Differentiation characteristic 2 - Sales Display

### Software

Update with flash-controller technology

### Safety

REACH conform Yes

RoHS conform Yes

Halogen free No

Protection with dismantling protection

Alarm alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

### Use conditions

Operating temperature -5...45 °C

Temperature temperature measurement via internal and/or external sensor with mean value formation

Energy efficiency class IV (2%)

### Identification

Application, usage KNX - operating systems

Product family product family: push-button

Main design line

KNX - Berker K.1/K.5

Secondary design line(s)

KNX ; Berker K.5

---

**Instructions**

Special note text

Use only in combination with frame frame with large cut-out.