



75664590



$\ensuremath{\mathsf{B.IQ}}$ push-button 4gang thermostat, display, KNX - $\ensuremath{\mathsf{B.IQ}}$, glass p. white

Technical characteristics

Functions	
With room temperature controller	Yes
Function	with valve protection function
Timers	with room temperature timer and 2-week timer functions
Compatibility	
Extension unit	extension unit for light scene push-button
Controls and indicators	
With LED indication	Yes
Number of buttons	4
Operation	one push-button operation for switching, pushing, shutters and dimming
Dimensions	
Assembling height	16.7 mm
Width of rail mounted device (RMD)	0 modules
Height	149.2 mm
Width	88.5 mm
Measurement	
Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
Screen	
With display	Yes
Materials	
Colour of design line	glass polar white
RAL colour	RAL 9010 - Pure white
Material	glass
Material family	Glass
LED control	
LED	with blue operation LED and 8 white status LEDs (labelling field illumination)
Settings	
Parameterisation	single and two push-button operation parameterisable

Accessories included

Box	for installation in single standard wall boxes
	for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x, for glass frames in the same "style" for additional applications, see the
Matching products	Design line B.7
Equipment	
Number of actuation points	10
Product type:	product type: B.IQ
Control	for individual single room temperature control
Software	
Update	with flash-controller technology
Safety	
Protection	with dismantling protection
Use conditions	
Operating temperature	-545 °C
Energy efficiency class	IV (2%)
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Release issue	2.6
Main design line	KNX - Berker B.IQ

KNX, Berker B.IQ

Secondary design line(s)