



75665590



$\ensuremath{\mathsf{B.IQ}}$ push-button 5gang thermostat, display, KNX - $\ensuremath{\mathsf{B.IQ}}$, glass p. white

Technical characteristics

Functions	
With room temperature controller	Yes
Function	with valve protection function
	with room temperature timer and 2-week timer
Timers	functions
Compatibility	
Extension unit	extension unit for light scene push-button
Controls and indicators	
With LED indication	Yes
Number of buttons	5
Operation	one push-button operation for switching, pushing, shutters and dimming
Dimensions	
Assembling height	16.7 mm
Width of rail mounted device (RMD)	0 modules
Height	178.8 mm
Width	88.5 mm
Measurement	
Value transmitter	value transmitter for dimming, position, brightness and temperature values 1 and 2 byte
Screen	
With display	Yes
Materials	
Colour of design line	glass polar white
RAL colour	RAL 9010 - Pure white
Material	glass
Material family	Glass
Settings	
Parameterisation	single and two push-button operation parameterisable
Scope of delivery	
Bus connection included	No
Accessories included	

for installation in single standard wall boxes

Box

for glass frames in the same "style" for additional applications, see the Design line B.7, for additional products to complement the installation in matching colours/materials, refer to the Design platform S.1/B.x

Matching products

Equipment	
Product type:	product type: B.IQ
Control	for individual single room temperature control
Software	
Update	with flash-controller technology
Safety	
Protection	with dismantling protection
Use conditions	
Operating temperature	-545 °C
Energy efficiency class	IV (2%)
Identification	
Application, usage	KNX - operating systems
Product family	product family: push-button
Release issue	2.6
Main design line	KNX - Berker B.IQ
Secondary design line(s)	Berker B.IQ, KNX